

DTX 2500 ICLEAN dust collector is a machine suitable for continuous use involving large quantities of material with a large filter surface area. It is equipped with an automatic filter cleaning system for the cartridges, which guarantees that the filtering capacity is always efficient, without stopping the machine. It is particularly suitable for use with machines in production.

TECHNICAL FEATURES **DTXLINE ICLEAN**

MODELS DTX 2500 ICLEAN

| | |
|---------------|---------------------|
| MOTORIZATION | Centrifugal fan |
| POWER | 5,5 kW |
| VOLTAGE | 400 V |
| FREQUENCY | 50 Hz |
| AMPERAGE | 16 A |
| AIRFLOW | 2500 m³/h |
| DEPRESSION | 44 mBar |
| Ø NOZZLE | Tangential Ø 150 mm |
| BODY DIAMETER | Ø 560 mm |
| DIMENSIONS | 146x84x175 cm |
| WEIGHT | 210 Kg |

FILTERING SYSTEM DTX 2500 ICLEAN

| | |
|-------------------------|----------------|
| FILTER TYPE | Cartridge |
| PRIMARY FILTER- SURFACE | 50.000 cm² |
| FILTER MEDIA | M + Antistatic |
| SECONDARY FILTER | OPT |
| FILTER CLEANING | Automatic |

COLLECTION SYSTEM DTX 2500 ICLEAN

| | |
|----------|-------------|
| CAPACITY | Barrel 100l |
|----------|-------------|



- ◀ Suction always present and efficient
- ◀ 5 HEPA cartridge filters + PTFE membrane for standard models
- ◀ 5 conductive HEPA cartridge filters for ATEX models
- ◀ Filter guard for improved cyclonic efficiency and protection from abrasive materials
- ◀ Fully automatic filter protection as standard



- ◀ Easy barrel release system



- ▶ Tangential inlet
- ▶ Available in ATEX version

