

The Basic models WT 155 and BT 155 are vacuum cleaners that are used in all areas of application for the general suction of dust, solids and liquids. Their motorisation with a 5.5 kW side channel turbine makes them reliable models even for continuous services and a safe investment to be entrusted with the daily cleaning services of every company.

TECHNICAL FEATURES **HDC BASIC**

**MODELS** B 155 P W 155 P B 155 S W 155 S

|                |                    |                   |                    |                   |
|----------------|--------------------|-------------------|--------------------|-------------------|
| MOTORIZATION   | Turbine            | Turbine           | Turbine            | Turbine           |
| POWER          | 5,5 kW             | 5,5 kW            | 5,5 kW             | 5,5 kW            |
| VOLTAGE        | 400 V              | 400 V             | 400 V              | 400 V             |
| FREQUENCY      | 50 Hz              | 50 Hz             | 50 Hz              | 50 Hz             |
| AMPERAGE       | 10,4 A             | 10,4 A            | 10,4 A             | 10,4 A            |
| AIR FLOW       | 520 m³/h           | 520 m³/h          | 320 m³/h           | 320 m³/h          |
| DEPRESSION     | 250 mBar           | 250 mBar          | 450 mBar           | 450 mBar          |
| MAX DEPRESSION | 320 mBar           | 320 mBar          | 530 mBar           | 530 mBar          |
| Ø NOZZLE       | Tangential Ø 60 mm | Central Ø 70 mm   | Tangential Ø 60 mm | Central Ø 60 mm   |
| BODY DIAMETER  | ø 460 mm           | ø 460 mm          | ø 460 mm           | ø 460 mm          |
| DIMENSIONS     | 100 x 60 x 140 cm  | 100 x 60 x 140 cm | 100 x 60 x 140 cm  | 100 x 60 x 140 cm |
| WEIGHT         | 150 Kg             | 150 Kg            | 150 Kg             | 150 Kg            |

**FILTERING SYSTEM** B 155 P W 155 P B 155 S W 155 S

|                          |                         |                         |                         |                         |
|--------------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| FILTER TYPE              | Stellar polyester       | Stellar polyester       | Stellar polyester       | Stellar polyester       |
| PRIMARY FILTER - SURFACE | 22.000 cm² / 30.000 cm² | 22.000 cm² / 30.000 cm² | 22.000 cm² / 30.000 cm² | 22.000 cm² / 30.000 cm² |
| STANDARD FILTER MEDIA    | L                       | L                       | L                       | L                       |
| SECONDARY FILTER         | OPT                     | OPT                     | OPT                     | OPT                     |
| FILTER CLEANING          | Manual shaking          | Manual shaking          | Manual shaking          | Manual shaking          |

**COLLECTION SYSTEM** B 155 P W 155 P B 155 S W 155 S

|                                    |                  |                  |                  |                  |
|------------------------------------|------------------|------------------|------------------|------------------|
| CAPACITY                           | 100l / Longopac® | 100l / Longopac® | 100l / Longopac® | 100l / Longopac® |
| LONGOPAC BARREL INTERCHANGEABILITY | YES              | YES              | YES              | YES              |



Available in **ATEX** version



Easy system for undocking the barrel

Longopac® continuous bag collection system

